



## Rope Characteristics

- Offer a wide range of constructions and diameters
- Manufactured predominantly with a natural fiber core
- Produced using softer grades of steel than ropes used in other markets
- Provide an average service life of eight to ten years




### 8x19 Classification

- Widely used in all elevator rope applications – hoist, compensating, governor, control, counterweight and car drum ropes
- Manufactured in Iron, Traction, Extra High Strength Traction grades
- Available in the following constructions:
  - 8x19 Warrington
  - 8x19 Seale (shown)
  - 8x21 Filler Wire
  - 8x25 Filler Wire
- Produced in right regular and Lang lays
- Manufactured with a natural fiber core



### 6x19 Classification

- Specified in some hoist, compensating and governor rope applications
- Manufactured in Iron, Traction, Extra High Strength Traction grades
- Available in the following constructions:
  - 6x19 Warrington
  - 6x25 Filler Wire (shown)
- Produced in right regular and Lang lays
- Manufactured with a natural fiber core



### Liftpac

- Recommended for use wherever elevator hoist ropes exhibit short service life due to adverse operating conditions (e.g. high groove pressures or loads, reverse bends) and/or fatigue breakage with minimal surface wear is the primary factor for rope retirement
- Manufactured in Traction and Extra High Strength Traction grades in an 8x19 Seale right Lang lay fiber core construction
- Produced with compacted strands
- Available in 3/8", 1/2" and 5/8" diameters

# Elevator Wire Ropes

For information on other diameters, constructions, lay and cores not listed below, please contact WW's Customer Service Department.

ROPE DIAMETER		APPROXIMATE WEIGHT (lb./ft.)			NOMINAL STRENGTH (tons)*							
inches	mm.				6x19 CLASS			8x19 CLASS			LIFTAC	
		6x19 Class	8x19 Class	Liftpac	Extra High Traction	Traction Steel	Iron	Extra High Traction	Traction Steel	Iron	Extra High Traction	Traction Steel
1/4	6.5	0.10	0.09	--	2.6	1.8	1.1	2.25	1.80	.90	--	--
5/16	8.0	0.16	0.14	--	4.1	2.8	1.6	3.45	2.80	1.45	--	--
3/8	9.5	0.23	0.20	0.23	5.8	4.1	2.5	4.95	4.10	2.10	5.5	4.5
7/16	11.0	0.31	0.28	--	7.9	5.5	3.2	6.75	5.50	2.80	--	--
1/2	13.0	0.40	0.36	0.39	10.2	7.3	4.2	8.75	7.25	3.60	9.7	8.0
9/16	14.5	0.51	0.46	--	12.9	9.3	5.3	11.05	9.25	4.60	--	--
5/8	16.0	0.63	0.57	0.62	15.8	11.5	6.4	13.60	11.50	5.60	15.4	12.7
11/16	17.5	0.76	0.69	--	19.1	13.5	--	16.40	13.50	6.70	--	--
3/4	19.0	0.90	0.82	--	22.6	16.0	9.1	19.45	16.00	8.00	--	--
13/16	20.6	1.03	0.96	--	26.5	18.5	--	23.00	18.50	9.30	--	--
7/8	22.0	1.23	1.11	--	30.6	21.0	12.4	26.30	21.00	10.70	--	--
15/16	23.5	1.41	1.27	--	35.0	24.0	--	30.00	24.00	14.00	--	--
1	26.0	1.60	1.45	--	39.8	27.0	16.0	34.20	27.00	15.70	--	--
1-1/16	27.0	1.81	1.64	--	44.7	30.5	--	38.50	30.50	--	--	--

\*Acceptance strength is not less than 2-1/2% below the nominal strengths listed. Tons of 2,000 lbs.



**Wire Rope Works, Inc.**  
 manufacturer of Bethlehem Wire Rope®

100 Maynard Street  
 Williamsport Pennsylvania 17701 USA  
 telephone: 570-326-5146 facsimile: 570-327-4274  
[www.wireropeworks.com](http://www.wireropeworks.com)



Wire rope products will break if abused, misused or overused. Consult industry recommendations and OSHA Standards before using. Wire Rope Works, Inc. warrants all Bethlehem Wire Rope® and Strand products. However, any warranty, expressed or implied as to quality, performance or fitness for use of wire rope products is always premised on the condition that the published breaking strengths apply only to new, unused rope, that the mechanical equipment on which such products are used is properly designed and maintained, that such products are properly stored, handled, used and maintained, and properly inspected on a regular basis during the period of use. Manufacturer shall not be liable for consequential or incidental damages or secondary charges including but not limited to personal injury, labor costs, a loss of profits resulting from the use of said products or from said products being incorporated in or becoming a component of any product. Wire Rope Works, Inc. © 2010

Bethlehem Wire Rope®

